

2T SPECIALE

2 STROKE ENGINE-OIL SEMI-SYNTHETIC



GREEN AREAS RANGE
ENGINE
SEMI-SYNTHETIC

Mineral

Semi-synthetic

100%
synthetic



STANDARDS AND SPECIFICATIONS

API TC
JASO FD
ISO-L-EGD

APPLICATIONS

2T SPECIALE is a high performance oil specially recommended for chainsaws, for all 2 stroke aircooled engines working at very high temperatures and for all 2 stroke engines difficult to cool.

2T SPECIALE is also recommended for microlight engines.

2T SPECIALE can be used with unleaded (RON 95 and 98) or high-octane gasoline.

2T SPECIALE can also be used as a mixture or as a separated greasing for measuring pump.

Treat level : from 2 % and above, according to manufacturers recommended treat level. Add oil to petrol and not the other way round.

BENEFITS

- Meets the most severe 2 stroke engine specifications: API TC, JASO FD, ISO-L-EGD.
- Large thermal stability, preventing against piston blocking.
- Excellent resistance to oxidation preventing piston varnish.
- High detergency for engine cleanliness.
- Very low sulphated ash level, for the prevention of preignition, exhaust port blocking and catalyst compatibility in service
- Low smoke formation.

PERFORMANCES

PERFORMANCE LEVELS | API TC
JASO FD
ISO-L-EGD

CHARACTERISTICS

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
Colour	-	Visual	Red
Specific gravity at 15°C	kg/m ³	NF T 60-101	882
Kinematic viscosity at 100°C	mm ² /s	NF T 60-100	13,7
Sulfated ashes content	% mass	NF T 60-143	0,046
TBN	mg KOH/g	ASTM D 2896	1,16

This typical data is given for information only

OPAL
OPAL
OPAL
OPAL
OPAL



HEALTH, SAFETY AND ENVIRONMENT

Disposal methods must comply with current applicable regulations concerning the disposal of used oils.

Store in a sheltered area.

Our technical department is available to help and advise you if needed.