

## ALUMIX ULTRA

ANTI-SEIZE COMPOUND WITH ALUMINIUM POWDER BASE



### APPLICATIONS

**ALUMIX ULTRA** is specially formulated to prevent seizure and corrosion of metal assemblies that are subjected to very high temperatures (up to 800 °C), in order to facilitate their disassembly.

**ALUMIX ULTRA** is also recommended for the lubrication of bearings that operate at very low speeds (less than 3 m per minute) and at high temperatures.

### BENEFITS

- Easy to apply.
- Leaves a protective anti-corrosion film on the parts.
- Prevents all types of seizure on parts exposed to high temperatures.
- Unaffected by steam and high pressures.
- Supplied with a special application head for thick products, in order to avoid aerosol clogging problems.

### PRODUCT CHARACTERISTICS

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
Appearance	-	Visual	Smooth
Colour	-	Visual	Silver
Consistency	NLGI grade	NF T 60506	1
Penetrability at 25°C	1/10 mm	NF T 60132	285 / 310
Drip point	°C	NF T 60102	180

*This typical data is given for information only*

### AEROSOL CHARACTERISTICS

- Gross volume: 650 ml
- Net content: 500 ml
- Net weight: 322 g
- Weight of active product: 161 g
- Double ball valve for use in any position
- Supplied with 2 spray nozzles: 1 short (special for thick products) and 1 long

### HEALTH, SAFETY AND ENVIRONMENT

Only dispose of completely empty containers.

Disposal after use must comply with current applicable regulations.

Store in an area protected from the weather.

Our technical department is available to help and advise you if needed.

Propellant gas: butane (extremely flammable).