



BRAKE FLUID DOT 3

SYNTHETIC FLUID FOR THE CIRCUITS OF HYDRAULIC BRAKES

APPLICATIONS

BRAKE FLUID DOT 3 is recommended for all hydraulic brake and clutch circuits, needing a fluid which responds to the standards and specifications FMVSS 116 DOT 3 and SAE J 1703.

CAUTION : Must not be mixed with LHM fluids (Organs painted green). Keep the packaging firmly sealed, and use the product in the month following opening.

BENEFITS

- High security in case of the brakes overheating: high boiling point, even when water is present. The fluid stays incompressible.
- Security when freezing : **BRAKE FLUID DOT 3** absorbs and makes the condensation soluble.
- Long life of the circuit elements : **BRAKE FLUID DOT 3** is inhibited against the corrosion and is compatible with the elastomers.

BRAKE FLUID DOT 3 is miscible with all fluids of the same nature (DOT 4 and DOT 5.1)

BRAKE FLUID DOT 3 is not miscible with silicone products.

PERFORMANCES

PERFORMANCE
LEVELS

SAE J 1703
FMVSS 116, DOT 3

CHARACTERISTICS

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
Specific gravity at 20°C	kg/m ³	NF T 60-101	1060
Kinematic viscosity at 100°C	mm ² /s	NF T 60-100	1,5
Kinematic viscosity at -40°C	mm ² /s	NF T 60-100	1500
Boiling point	°C	FMVSS 116	> 205

This typical data is given for information only

HEALTH, SAFETY AND ENVIRONMENT

Elimination after use must be made in conformity with the rules in force about used oils throwing out.

Must be stored away from bad weather.

Should you need further details, our Technical Department remains at your entire disposal.