

# CHAIN GREEN BIODEGRADABLE CHAIN SAW OIL



# **APPLICATIONS**

**CHAIN GREEN** is an adhesive and biodegradable oil for the lubrication of electric or thermal engine chain saws.

**CHAIN GREEN** is coming from renewable resources that give it remarkable lubrication properties while preserving the environment.

#### **BENEFITS**

- Very quickly biodegradable: formulated from elaborated vegetable oils that guarantee the respect of the environment.
- Very adhesive and unctuous, it perfectly protects the guide and the chain against premature wear.
- Ropy, the oil adheres to the chain guide and thus limits its consumption.
- ➤ ISO grade 150 is particularly recommended by professionals working continuously during long periods.

**Caution:** UNIL OPAL recommends to drain your tank after use in case of non use during several weeks.

## **CHARACTERISTICS**

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA	
ISO grade	-	-	100	150
Kinematic viscosity at 40°C	mm²/s	NF T 60-100	104	155,8
Kinematic viscosity at 100°C	mm²/s	NF T 60-100	24,8	35,8
Viscosity index	-	NF T 60-136	270	276
Pour point	°C	NF T 60-105	-12	-12
Ecotoxicity on seaweeds	mg/l	OECD 201	> 1000	
Ecotoxicity on daphnies	mg/l	OECD 202	> 1000	
Ecotoxicity on fishes	mg/l	OECD 203	> 1000	
Biodegradability	%	CEC L-33-A-93	99	
Biodegradability	%	OECD 301 B	82	

This typical data is given for information only

### **HEALTH, SAFETY AND ENVIRONMENT**

Elimination must be carried out to conform to the rules set for the disposal of used oils.

#### Must be stored away from bad weather.

Should you need further details, our Technical Department remains at your entire disposal.

Storage time: 1 year.

