



CHAIN S ULTRA

100% SYNTHETIC LUBRICANT FOR CHAINS



APPLICATIONS

CHAIN S ULTRA is a lubricant and a polyvalent conservation agent, entirely synthetic and from exceptional quality.

CHAIN S ULTRA is used in industry and mechanic workshops. It can be used to clean and to lubricate easily chains, hinges, bolts, springs, locks, articulated joints, wrapping cables (Bowden), slide-bars, small gears, etc...

Operating temperature range : -30°C to +200°C.

BENEFITS

- It sticks perfectly.
- Resists to pressures and elevated temperatures.
- It protects very well against corrosion.
- Resists against water projections.
- Avoids the lengthening of chains.

PRODUCT CHARACTERISTICS

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
Appearance	-	Visual	Clair
Type	-	-	Polyalkylene glycol and chemical additives
Specific gravity at 20°C	kg/m ³	NF T 60-101	1 003
Viscosity at 40°C	mm ² /s	NF T 60-100	318,7
Flash point	°C	NF T 60-118	250

This typical data is given for information only

AEROSOL CHARACTERISTICS

- Gross volume : 650 ml
- Net content : 500 ml
- Net weight : 394 g
- Weight of active product : 276 g
- Double ball bearing valve for use in different positions.
- Supplied with 2 spray heads : 1 short (mini jet) and 1 long.

HEALTH, SAFETY AND ENVIRONMENT

Only throw away empty containers. Elimination after use must be made conforming the rules in force.

Store in an area protected from the weather.

Our technical department is available to help and advise you if needed.

Propellant gas : butane / propane (extremely flammable).