

COMPRESSOR P

LUBRICANT FOR RECIPROCATING COMPRESSORS



APPLICATIONS

COMPRESSOR P are specially formulated to lubricate reciprocating air compressors as well as than vacuum pumps.

COMPRESSOR P 100 is more particularly adapted for lubricating some rotary vane compressors.

BENEFITS

COMPRESSOR P is formulated with selected mineral base oils to :

- reduce carbon deposits and varnish
- resist to oxidation
- have a low volatility
- have a high flash point.

Special additives give to **COMPRESSOR P** very good anti-wear and anti-rust properties.

PERFORMANCES

PERFORMANCE LEVELS | DIN 51506 VBL, VCL, VDL

CHARACTERISTICS

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA		
ISO grade	-	-	68	100	150
Specific gravity at 15°C	kg/m ³	NF T 60-101	879	883	887
Kinematic viscosity at 40°C	mm ² /s	NF T 60-100	65,5	94,9	149,5
Kinematic viscosity at 100°C	mm ² /s	NF T 60-100	8,6	11	14,8
Viscosity index	-	NF T 60-136	102	101	98
Pour point	°C	NF T 60-105	-33	-30	-21
Flash point	°C	NF T 60-118	224	246	256
Pneurop Oxidation Test (POT) (Conradson increase)	%	DIN 51352/2	< 3		

This typical data is given for information only

HEALTH, SAFETY AND ENVIRONMENT

Elimination after use be made in conformity with the rules in force about used oils throwing out.

Must be stored away from bad weather.

Should you need further details, our Technical Department remains at your entire disposal.