

COMPRESSOR PAS

100% SYNTHETIC LUBRICANTS FOR RECIPROCATING COMPRESSORS



APPLICATIONS

COMPRESSOR PAS are specially recommended for the lubrication of all reciprocating air compressors, particularly when the discharge temperature is between 160°C and 220°C.

COMPRESSOR PAS 100 is more particularly adapted for lubricating some rotary vane compressors.

BENEFITS

Security:

Great reduction of fire and explosion hazards.

COMPRESSOR PAS, 100 % synthetic, reduce carbon deposits and varnish on discharge pistons and valves.

Longevity - Saving:

The exceptional resistance to oxidation of **COMPRESSOR PAS** allows very high discharge temperatures and longer oil change intervals.

PERFORMANCES

PERFORMANCE LEVELS | DIN 51506, classes VBL, VCL, VDL
ISO L DAA, DAB, DAC

CHARACTERISTICS

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA	
ISO grades	-	-	68	100
Specific gravity at 15°C	kg/m ³	NF T 60-101	860	854
Kinematic viscosity at 40°C	mm ² /s	NF T 60-100	71,8	98,1
Kinematic viscosity at 100°C	mm ² /s	NF T 60-100	10,5	13,6
Viscosity index	-	NF T 60-136	132	139
Flash point	°C	NF T 60-118	240	236
Pour point	°C	NF T 60-105	-39	-39

This typical data is given for information only

HEALTH, SAFETY AND ENVIRONMENT

Elimination must be carried out to conform to the rules set for the disposal of used oils.

Must be stored away from bad weather.

Should you need further details, our Technical Department remains at your entire disposal.