

# COMPRESSOR VR

LUBRICANT FOR ROTARY AIR COMPRESSORS



## APPLICATIONS

COMPRESSOR VR are formulated based mineral oil recommended for the lubrication of screw or paddle rotary air compressors..

## BENEFITS

- Slight tendency to form deposits
- Exceptional resistance to oxidation
- Low volatility
- Excellent anti-wear and anti-corrosion properties

## PERFORMANCES

PERFORMANCE LEVEL | ISO 6743-3 A DAG/DAH

## CHARACTERISTICS

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA		
ISO grade	-	-	32	46	68
Specific gravity at 15°C	kg/m <sup>3</sup>	NF T 60-101	870	876	880
Kinematic viscosity at 40°C	mm <sup>2</sup> /s	NF T 60-100	32	46,9	67
Kinematic viscosity at 100°C	mm <sup>2</sup> /s	NF T 60-100	5,5	6,9	8,6
Viscosity index	-	NF T 60-136	108	102	99
Pour point	°C	NF T 60-105	-30	-30	-24
Flash point	°C	NF T 60-118	222	230	240

*This typical data is given for information only*

## HEALTH, SAFETY AND ENVIRONMENT

Elimination must be carried out to conform to the rules set for the disposal of used oils.

Must be stored away from bad weather.

Should you need further details, our Technical Department remains at your entire disposal.

UNIL  
 OPAL  
 UNIL  
 OPAL  
 UNIL  
 OPAL  
 UNIL  
 OPAL