

DEMOULSIL ULTRA

SILICONE MOULD RELEASING AGENT





APPLICATIONS

DEMOULSIL ULTRA is a mould-releasing agent for injection-moulded parts made of all types of plastic.

BENEFITS

- Guarantees easy mould removal.
- Provides a clean, smooth surface.

<u>Caution</u>: The product contains silicone. For this reason, the parts must be very carefully cleaned before any painting, bonding or pad-printing operations.

PRODUCT CHARACTERISTICS

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
Colour	-	Visual	Colourless
Туре	-	-	Silicone oil
Specific gravity at 20°C	kg/m³	NF T 60-101	970
Flash point	°C	NF T 60-118	315

This typical data is given for information only

AEROSOL CHARACTERISTICS

Gross volume : 650 ml
Net content : 500 ml
Net weight : 297 g

> Weight of active product: 90 g

Double-bearing valve for multi-position use.

Delivered with 2 distribution heads: 1 standard and 1 long.

HEALTH, SAFETY AND ENVIRONMENT

Only throw away empty containers. Elimination after use must be made conforming the rules in force.

Store in an area protected from the weather.

Our technical department is available to help and advise you if needed.

Propellant gas: butane / propane (extremely flammable).

