

FOOD GREASE ULTRA

MULTI-USE GREASE FOR FOOD CONTACT



APPLICATIONS

FOOD GREASE ULTRA is a lubricating product and an anti-corrosion protection product for operating equipments in food and water industries.

Although the components of this grease are considered as non toxic agents, it is advised to avoid too abundant greasing.

FOOD GREASE ULTRA allows the clean greasing of hardly accessible parts: chains, springs, hinges, cables, slides.

FOOD GREASE ULTRA is also used for the greasing of bearings, warp bearings and articulations.

Operating temperature range: -20°C to +120°C, 140°C at the peak.

BENEFITS

- The components meet the requirements of the FDA, section 21 CFR 178.3570 **for food contact**.
- The active material is homologated NSF-H1 (N°126882) for casual contact with food.
- Very good resistance to water, even to warm water, to diluted acids and alkaline lye, even to aggressive waste waters.
- Penetrates rapidly and forms a lubricating film which reduces the wear of the machines and ensures a lasting protection against oxidation and corrosion.

PRODUCT CHARACTERISTICS

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
Type of soap	-	-	Complex aluminium
Colour	-	Visual	Light beige
Consistency	NLGI	NF T 60-506	2
Penetration at 25°C after 60 strokes	1/10 mm	NF T 60-132	265 / 295
Viscosity of basic oil at 40°C	mm²/s	NF T 60-100	140
Dropping point	°C	NF T 60-102	> 230
Operating temperature range	°C	-	-20 / +120

This typical data is given for information only

AEROSOL CHARACTERISTICS

- Gross volume : 650 ml
- Net content : 500 ml
- Net weight : 320 g
- Weight of active product : 128 g
- Double-bearing valve for multi-position use.
- Delivered with 2 distribution heads : 1 short (minijet) and 1 medium (middlejet).



HEALTH, SAFETY AND ENVIRONMENT

Only throw away empty containers. Elimination after use must be made conforming the rules in force.

Store in an area protected from the weather.

Our technical department is available to help and advise you if needed.

Propellant gas : butane (extremely flammable).