



GEAR OUTBOARD 80W90

MARINE GEAR OIL

APPLICATIONS

GEAR OUTBOARD 80W90 is an extreme pressure oil formulated for outboard motors and drives.

GEAR OUTBOARD 80W90 is suitable for Mercury Marine transmissions recommending an API GL-5 standard.

BENEFITS

- High anti-wear power
- Very good resistance to oxidation
- Reinforced anti-rust and anti-corrosion protection
- Anti-foam

PERFORMANCES

PERFORMANCE LEVELS | API GL-5, API GL-4
MIL L 2105 D

CHARACTERISTICS

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
SAE grade	-	-	80W-90
Specific gravity at 20°C	kg/m ³	NF T 60-101	899
Kinematic viscosity at 40°C	mm ² /s	NF T 60-100	154
Kinematic viscosity at 100°C	mm ² /s	NF T 60-100	15,6
Viscosity index	-	NF T 60-136	110
Flash point	°C	NF T 60-118	222
Pour point	°C	NF T 60-105	-30

This typical data is given for information only

HEALTH, SAFETY AND ENVIRONMENT

Disposal must be carried out in accordance with regulations in effect for the disposal of used mineral oils.

Must be stored away from bad weather conditions.

For further details, our Technical Department can provide assistance if necessary.

OPAL
7220
7111
7220
OPAL
7220
7111
OPAL
7220
7111