



GERION DE 75W

100% SYNTHETIC LUBRICANT FOR VL GEARBOXES



TRANSMISSION RANGE

BVM GEARBOXES
100% SYNTHETIC
SAE 75W

Mineral

Semi-synthetic

100%
synthetic

STANDARDS & SPECIFICATIONS

API GL-4
FORD WWS-M2C200-D2
VW G 052 726
VW G 052 512

Oxidation resistance



Shear stability



Extreme pressure level



APPLICATIONS

GERION DE 75W is a 100% synthetic fluid compatible with most light duty vehicles requiring API GL-4 performance levels.

GERION DE 75W is recommended for gear boxes that meet the standards for FORD WSS-M2C200-D2 and Volkswagen gear boxes.

GERION DE 75W is compatible with gear gear boxes equipped with Carbon or Molybdenum synchronizers.

BENEFITS

- Excellent fluidity at low temperatures facilitating gear changes when starting the vehicle, even in the coldest conditions
- Excellent friction resistance: compatible with synchronizers of recent gear boxes.
- Low viscosity resulting in better lubrication of the gear box
- Good resistance to oxidation allowing use at high temperatures
- Excellent corrosion protection

PERFORMANCES

PERFORMANCE LEVELS

- API GL-4
- BMW MTF LT-3
- FORD WSS-M2C200-D2
- VW G 052 178 – 052 512 – 052 726 – 055 512 A2 – 060 726
- VW GO 52 527 A2 - 70 726 A2
- TRANSELF NFX

EXPERIENCE IN OPERATIONAL USE

- FIAT MZ7
- PSA 2316 (Part number - PSA 16 180 784 80) / 9730 A8
- BOT 350 M3
- RENAULT DC4 DW5 (Dry DCT)

Do not use GERION DE 75W when API GL-5 level is required.

OPAL
VW
OPAL
VW
OPAL
VW



CHARACTERISTICS

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
SAE grade	-	-	75W
Density at 15°C	kg/m ³	NF T 60-101	862
Kinematic viscosity at 40°C	mm ² /s	NF T 60-100	32.9
Kinematic viscosity at 100°C	mm ² /s	NF T 60-100	5.67
Viscosity index	-	NF T 60-136	112
Brookfield viscosity at -40° C	mPa.s	NF T 60-152	47 563
Pour point	°C	NF T 60-105	-42
Flash point	°C	NF T 60-118	212

The typical data provided are only approximate values

HEALTH, SAFETY AND ENVIRONMENT

Disposal must be done in compliance with the regulations in effect relating to the disposal of used oils.

Store in areas that are not exposed to bad weather conditions.

Our technical department is available to provide advice if needed.