



GERION DRIVE LS 75W140

100% SYNTHETIC LUBRICANT FOR GEARBOXES AND AXLES

TRANSMISSION RANGE

BVM GEARBOXES and AXLES
AXLES LS (limited slip differentials)
FULL SYNTHETIC
SAE 75W-140

Mineral

Semi-synthetic

100%
synthetic

STANDARDS AND SPECIFICATIONS

API GL-4 / GL-5 LS
API MT1
SCANIA STO 1:0
VOLVO 97315
ZF TE-ML 05D, 12D, 21B

Oxidation resistance

Shear stability

Extreme-pressure level



APPLICATIONS

GERION DRIVE LS 75W140 is a 100% synthetic lubricant specifically developed to lubricate heavy-use gearboxes and axles fitted in industrial vehicles, public works, or farming vehicles.

GERION DRIVE LS 75W140 is especially recommended for lubricating self-locking or limited slip differentials.

GERION DRIVE LS 75W140 successfully passed the CEC-L-48-A-95 oxidation test required for the thorough lubrication of RVI P 1370 rear axles.

BENEFITS

- 100% synthetic for outstanding resistance to oxidation:
 - guaranteed exceptional product longevity, enabling significant extensions in oil change intervals
 - utilisation even at the highest temperatures attained by modern transmissions
- Excellent resistance to shearing, ensuring maintenance of product performance throughout its entire life
- Extreme-pressure performance and reinforced anti-wear properties for effective resistance at very high loads
- Compatibility with non-ferrous metals
- Very good viscosity index for excellent fluidity at low temperatures and increased viscosity in hot temperatures
- Chatter-free silent operation of self-locking systems
- Energy savings

PERFORMANCE

PERFORMANCE LEVELS

API GL-4/ GL-5 LS
API MT1
RENAULT TRUCKS GL5 HT
SAE J2360
SCANIA STO 1:0
VOLVO 97315
ZF TE-ML 05D, 12D, 21B

OPAL
75W
140



CHARACTERISTICS

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
SAE grade	-	-	75W-140
Density at 15°C	kg/m3	NF T 60101	870
Kinematic viscosity at 40°C	mm ² /s	NF T 60100	204
Kinematic viscosity at 100°C	mm ² /s	NF T 60100	28.7
Viscosity index	-	NF T 60136	180
Brookfield viscosity at -40°C	mPa.s	NF T 60152	< 150 000
Pour point	°C	NF T 60105	-48
Flash point	°C	NF T 60118	160

The above data are provided on an indicative basis only.

HEALTH, SAFETY AND ENVIRONMENT

Disposal must be carried out in compliance with the rules governing the disposal of used lubricants.

Must be stored away from bad weather conditions.

For further details, our Technical Department is available to assist you

75W-140
75W-140
75W-140
75W-140