



GREASE 182 DS

MULTIPURPOSE GREASE



RANGE OF GREASES

NLGI 2
WATER RESISTANT
MULTIPURPOSE

Grade

2

-20°C/+120°C

max 130°C

APPLICATIONS

Speed: medium to high
Load: moderate

Extreme-pressure level

APPLICATIONS

GREASE 182 DS is an excellent grease for all current uses of moderate loads (joints, gimbals, pumps, bearings etc...).

BENEFITS

- Good lubricating power
- Smoothness and reinforced anti-wear power
- Very good functioning under any working condition
- Ease of injectability with all pressure distribution equipment
- Good anti-rust and anti-corrosion protection

CHARACTERISTICS

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
Soap	-	-	Lithium
Basic oil	-	-	Mineral oil
Texture	-	-	Smooth
Colour	-	Visual	Light yellow
NLGI Grade	-	ASTM D 217	2
Drop point	°C	IP 396	> 190
Kinematic viscosity at 40°C	mm ² /s	ASTM D 7152	110
Kinematic viscosity at 100°C	mm ² /s	ASTM D 7152	12
Penetration 60 strokes	1/10 mm	ISO 2137	265-295
4 ball welding	Kg	ASTM D 2596	200
Water jet resistance at 79°C	%	ISO 11009	< 10
Temperature range	°C	-	-20 / +120 (max 130)

The above data are provided on an indicative basis only.

HEALTH, SAFETY AND ENVIRONMENT

Disposal must be carried out in compliance with the rules governing the disposal of used lubricants.

Must be stored away from bad weather conditions.

For further details, our Technical Department is available to assist you.