

HUILE MOTEUR 4T EV

MOTOCULTIVATORS, MOWERS



GREEN AREAS RANGE
ENGINE
MINERAL
SAE 30

STANDARDS AND SPECIFICATIONS
API SF

Mineral

Semi-synthetic

100% synthetic



APPLICATIONS

Lubricant particularly well adapted to small petrol engines fitted to motorised gardening equipment.

BENEFITS

- Increased protection against bearings made of ferrous or non-ferrous metals.
- Rust-proof protection.
- Excellent resistance to high temperatures.
- Facilitates starting.

PERFORMANCES

PERFORMANCE LEVEL | API SF

CHARACTERISTICS

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
SAE grade	-	-	SAE 30
Specific gravity at 15°C	kg/m ³	NF T 60-101	884
Kinematic viscosity at 40°C	mm ² /s	NF T 60-100	76,7
Kinematic viscosity at 100°C	mm ² /s	NF T 60-100	9,8
Viscosity index	-	NF T 60-136	107
Pour point	°C	NF T 60-105	-33
Flash point	°C	NF T 60-118	236

This typical data is given for information only

HEALTH, SAFETY AND ENVIRONMENT

Disposal methods must comply with current applicable regulations concerning the disposal of used oils.

Store in a sheltered area.

Our technical department is available to help and advise you if needed.

OPAL
 75W
 OPAL
 75W
 OPAL
 75W
 OPAL
 75W