



HYDRO NET

ADDITIVE FOR CLEANING HYDRAULIC SYSTEMS



APPLICATIONS

HYDRO NET is a specially formulated supplement to dislodge gums and varnishes from hydraulic systems, and disperse them in the operating fluid.

BENEFITS

- **HYDRO NET** enables the system to be cleaned without stopping the machine, and therefore without any loss of production.
- **HYDRO NET** has a flash point of 164 °C, and can therefore advantageously replace solvents in cases where the use of solvents would be dangerous.

UTILISATION

- **HYDRO NET** is added to the charge of hydraulic oil in service, to a proportion of 5 to 15 %.
- Then run the installation normally for 12 to 48 hours, depending on the extent of fouling and on the consistency of the deposits.
- During this operation, the filters must be regularly checked and cleaned.
- When the operation has been completed, drain the system and eliminate any deposits that have agglomerated in the areas that are not flushed by the flow of fluid (dead zones of the system, or storage tanks).
- Replace the filters and then refill with the appropriate UNIL OPAL hydraulic oil for your equipment.

CHARACTERISTICS

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
Specific gravity at 15°C	Kg/m ³	NF T 60-101	881
Kinematic viscosity at 40°C	mm ² /s	NF T 60-100	45
Flash point	°C	NF T 60-103	164
Aniline point	°C	NF M 07021	76

This typical data is given for information only

HEALTH, SAFETY AND ENVIRONMENT

Irritant for the eyes: avoid contact with the eyes.

Disposal after use must comply with current applicable regulations concerning the disposal of used oils.

Store in a sheltered area.

Our technical department is available to help and advise you if needed.