

INTERCOOLER 375 10W30



CAR / TRUCK LUBRICANT FOR DIESEL AND PETROL ENGINES

INDUSTRIAL VEHICLES RANGE

ENGINE
MINERAL
SAE 10W-30

Mineral

Semi-synthetic

100% synthetic

STANDARDS AND SPECIFICATIONS

ACEA E2/A2/B2
API CF4/SG

Engine cleanliness

Oxidation resistance

Shear stability



APPLICATIONS

INTERCOOLER 375 10W30 has been designed to lubricate a very wide range of **diesel or petrol** aspirated or turbo-charged engines, in all seasons.

BENEFITS

- High detergent power
- Thermal stability
- Strengthened anti-corrosion and anti-rust protection
- Very low pour point

PERFORMANCES

PERFORMANCE LEVELS

ACEA E2/A2/B2
API CF4/SG
MAN 271
MB 228.1/229.1
VOLVO VDS

CHARACTERISTICS

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
SAE grade	-	-	10W-30
Specific gravity at 15°C	kg/m ³	NF T 60-101	874
Kinematic viscosity at 40°C	mm ² /s	NF T 60-100	80,8
Kinematic viscosity at 100°C	mm ² /s	NF T 60-100	12
Viscosity index	-	NF T 60-136	143
Pour point	°C	NF T 60-105	-33
Flash point	°C	NF T 60-118	232

This typical data is given for information only

UNIL
 OPAL
 UNIL
 OPAL
 UNIL
 OPAL
 UNIL
 OPAL



HEALTH, SAFETY AND ENVIRONMENT

Elimination must be carried out to conform to the rules set for the disposal of used lubricants.

Must be stored away from bad weather.

Should you need further details, our Technical Department remains at your entire disposal.