



INTERCOOLER 375 15W40



CARS AND TRUCKS LUBRICANT FOR DIESEL AND PETROL ENGINES

INDUSTRIAL VEHICLES RANGE

ENGINE
MINERAL
SAE 15W-40

Mineral

Semi-synthetic

100% synthetic

STANDARDS AND SPECIFICATIONS

ACEA E2/A2/B2
API CF-4/SJ
MAN 271
MB 228.1/229.1
VOLVO VDS

Engine cleanliness



Oxidation resistance



Shear stability



APPLICATIONS

INTERCOOLER 375 15W40 has been designed to lubricate a very wide range of **diesel or petrol aspirated or turbo-charged engines**, in all seasons.

INTERCOOLER 375 15W40 is ideally suited to mixed fleets with both cars and trucks.

BENEFITS

- High detergent power
- Thermal stability
- Strengthened anti-corrosion and anti-rust protection
- Very low pour point

PERFORMANCES

PERFORMANCE LEVELS

ACEA E2/A2/B2
API CF-4/SJ
MAN 271
MB 228.1/229.1
VOLVO VDS

CHARACTERISTICS

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
SAE grade	-	-	15W-40
Specific gravity at 15°C	kg/m ³	NF T 60-101	887
Kinematic viscosity at 40°C	mm ² /s	NF T 60-100	104,6
Kinematic viscosity at 100°C	mm ² /s	NF T 60-100	14
Viscosity index	-	NF T 60-136	133
Pour point	°C	NF T 60-105	-39
Flash point	°C	NF T 60-118	234
TBN	mg KOH/g	ASTM D 2896	8,5

This typical data is given for information only

OPAL
 75W
 75W
 OPAL
 75W
 75W



HEALTH, SAFETY AND ENVIRONMENT

Elimination must be carried out to conform to the rules set for the disposal of used lubricants.

Must be stored away from bad weather.

Should you need further details, our Technical Department remains at your entire disposal.