

KUTILUB A 23

CHLORINE-FREE CUTTING LUBRICANT



APPLICATIONS

- **KUTILUB A 23** is a lubricant specially designed for centerless grinding on steel, stainless-steel and titanium.

BENEFITS

- Ensures optimal cooling.
- Prevents the formation of oil mist.
- Extreme pressure.
- Anti-wear.
- Anti-foam.
- Anti-fog.

CHARACTERISTICS

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
Appearance	-	Visual	Clear
Colour	-	Visual	Pale yellow
Density at 15°C	kg/m ³	NF T 60-101	903
Kinematic viscosity at 40°C	mm ² /s	NF T 60-100	27.3
Flash point	°C	NF T 60-118	> 164
4-ball weld test	daN	NF E 48617	450

The typical characteristics provided are only approximate values

HEALTH, SAFETY AND ENVIRONMENT

KUTILUB A 23 is made from new, non-regenerated oils, exempt from the CAP.

KUTILUB A 23 is not affected by the voluntary labelling rules established by the UFIP.

Disposal must be carried out in accordance with applicable rules on the disposal of used machining fluids.

Must be stored in a FROST FREE environment away from any BAD WEATHER conditions.

Our technical department is available to provide any advice you may need.