

KUTILUB C 192

CHLORINE-FREE CUTTING LUBRICANT



APPLICATIONS

- **KUTILUB C 192** is a lubricant specially designed for all bar turning, turning, truing and planing type chip removal operations on steels and non-ferrous metals (copper, aluminium and light alloys).

BENEFITS

- Long bath and tool life
- Allows high cutting and feeding speeds
- Ensures optimal cooling
- Does not stain yellow metals
- Very low odour
- Excellent oxidation resistance
- Extreme pressure
- Anti-wear
- Greater smoothness
- Anti oil mist

CHARACTERISTICS

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
Appearance	-	Visual	Clear
Colour	-	Visual	Light yellow
Density at 15°C	kg/m ³	NF T 60-101	858
Kinematic viscosity at 40°C	mm ² /s	NF T 60-100 or Houillon	19.2
Flash point	°C	NF T 60-118	186
Copper corrosion	Rating	NF M 07015	1b
4-ball weld test	daN	NF E 48617	250

The typical characteristics provided are only approximate values

HEALTH, SAFETY AND ENVIRONMENT

KUTILUB C 192 is made from new, non-regenerated oils, exempt from the CAP.

KUTILUB C 192 is not affected by the voluntary labelling rules established by the UFIP.

Disposal must be carried out in accordance with applicable rules on the disposal of used machining fluids.

Must be stored in a FROST FREE environment away from any BAD WEATHER conditions.

Our technical department is available to provide any advice you may need.

UNIL
 OPAL
 UNIL
 OPAL
 UNIL
 OPAL
 UNIL
 OPAL