

# KUTILUB C 200

CHLORINE-FREE CUTTING LUBRICANT



## APPLICATIONS

- **KUTILUB C 200** is a lubricant specially designed for all bar turning, turning, truing and planing type chip removal operations on steels and non-ferrous metals (copper, aluminium and light alloys).

## BENEFITS

- Long bath and tool life
- Allows high cutting and feeding speeds
- Ensures optimal cooling
- Clearly noticeable extreme pressure power
- Anti-wear
- Greater smoothness
- Greater anti oil mist properties
- Does not stain copper or copper alloys

## CHARACTERISTICS

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
Appearance	-	Visual	Clear
Colour	-	Visual	Light yellow
Density at 15°C	kg/m <sup>3</sup>	NF T 60-101	870
Kinematic viscosity at 40°C	mm <sup>2</sup> /s	NF T 60-100 or Houillon	21.5
Flash point	°C	NF T 60-118	188
Copper corrosion	Rating	NF M 07015	1b
4-ball weld test	daN	NF E 48617	400

*The typical characteristics provided are only approximate values*

## HEALTH, SAFETY AND ENVIRONMENT

**KUTILUB C 200** is made from new, non-regenerated oils, exempt from the CAP.

**KUTILUB C 200** is not affected by the voluntary labelling rules established by the UFIP.

**KUTILUB C 200** may involve specific analytical monitoring if solvent degreasing with recycling by distillation is used in the process.

Disposal must be carried out in accordance with applicable rules on the disposal of used machining fluids.

Must be stored in a FROST FREE environment away from any BAD WEATHER conditions.

Our technical department is available to provide any advice you may need.