TECHNICAL DATA SHEET



KUTILUB GREEN



APPLICATIONS

KUTILUB GREEN is a **plant-based** very smooth oil for metal-working with the removal of shavings or deformation.

KUTILUB GREEN can be used as a micro-spray.



In the <u>wood processing sector</u>, **KUTILUB GREEN** is recommended for lubricating band saw blades, planer tables and moulders. Plant-based, **KUTILUB GREEN** is suitable for stave saw blades used in cooperage, and machine gun knives.

Thanks to its enhanced lubricity, it allows good saw performance while providing protection during use: high flash point and reduced soil pollution.

BENEFITS

- Extremely smooth.
- > Does not include toxic and silicone components.
- Biodegradable.
- High flash point
- > Miscible and compatible with mineral oils

CHARACTERISTICS

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
Colour	-	Visual	Blonde
Specific gravity at 15°C	kg/m ³	NF T 60-101	916
Kinematic viscosity at 40°C	mm²/s	NF T 60-100	36
Kinematic viscosity at 100°C	mm²/s	NF T 60-100	8
Viscosity index	-	NF T 60-136	206
Flash point	°C	NF T 60-118	310
Pour point	°C	NF T 60-105	-21
Biodegradability	%	CEC 133A93	98
Biodegradability	%	OECD 301B	> 87

This typical data is given for information only

HEALTH, SAFETY AND ENVIRONMENT

Elimination must be carried out to conform to the rules set for the disposal of used machining fluids.

Must be stored AWAY FROM FROST and FROM BAD WEATHER.

Should you need further details, our Technical Department remains at your disposal.

レイト

<u>www.unil-opal.com</u>