



LDA+ POWER STEERING FLUID



POWER STEERING FLUID
FULL SYNTHETIC FLUID
ESTER BASED

STANDARDS & SPECIFICATIONS

VW G 004 000
MB 345.0 / 236.3
FORD M2C204-A / M2C195-A
DEXRON® II-D/III



APPLICATIONS

LDA+ is a green coloured synthetic fluid for hydroelectric power stations, power steering, shock absorbers and active suspensions.

WARNING : do not use in CITROËN hydroelectric power stations as the circuits are painted in green.

BENEFITS

- Great operating range: from – 40°C to 140°C
- Excellent thermal stability
- Highly resistant to shearing

PERFORMANCE

PERFORMANCE LEVELS

CHRYSLER/DODGE/JEEP MS 1872
CHRYSLER/DODGE/JEEP MS 9602 (ATF+4)
CHRYSLER/DODGE/JEEP MS 11655
CHRYSLER/DODGE/JEEP MS 5931 (04883077)

FENDT X 902 011 622

FORD/LINCOLN/MERCURY M2C-204-A
FORD/LINCOLN/MERCURY M2C-195-A

GM/GMC/OPEL/SATURN DEXRON® II-D
GM/GMC/OPEL/SATURN DEXRON® III
GM/GMC/OPEL/SATURN 88901975 / 89021184
GM/GMC/OPEL/SATURN 9985010 / 1052884
GM/GMC/OPEL/SATURN 9985835 / 12345866

HYUNDAI / KIA PSF-3 / 4

MAN M 3289

MERCEDES/DAIMLER MB 236.3
MERCEDES/DAIMLER MB 345.0



TECHNICAL DATA SHEET

PERFORMANCE LEVELS

mitsubishi PS FLUID
mitsubishi DIAMOND SP III

NISSAN/INFINITY PSF-II

PENTOSIN CHF 7.1
PENTOSIN CHF 11S
PENTOSIN CHF 202

PSA S71 2710 (LDS)

SAAB 30 09 800 / 30 32 380

SUBARU K0209A0080
TOYOTA/LEXUS PSF Type EH

VOLKSWAGEN / AUDI / SEAT / SKODA VW G 002 000
VOLKSWAGEN / AUDI / SEAT / SKODA VW G 002 012
VOLKSWAGEN / AUDI / SEAT / SKODA VW G 004 000

VOLVO 116 1529

CHARACTERISTICS

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
Colour	-	-	green
Density at 15°C	kg/m ³	NF T 60-101	826
Kinematic viscosity at 40°C	mm ² /s	NF T 60-100	30
Kinematic viscosity at 100°C	mm ² /s	NF T 60-100	6,9
Viscosity index	-	NF T 60-136	201
Pour point	°C	NF T 60-105	-69
Flash point	°C	NF T 60-118	222
Brookfiel -40°C	mPa.s	NF T 60-100	4,343

The average specifications provided are approximate values

HEALTH, SAFETY AND ENVIRONMENT

Disposal must be carried out in compliance with applicable rules for the disposal of used oil.

Store in an area sheltered from bad weather.

Our technical department is available to give you any advice you may need.