



LHM S

SPECIAL HYDRAULIC LIQUID FOR HYDRAULIC CIRCUITS OF CITROEN VEHICLES

APPLICATIONS

LHM S is a fluid for the exclusive use in the hydraulic generators of CITROEN vehicles where the circuits are painted green.

LHM S acts as suspension, braking and steering assistance.

LHM S is forbidden in the mechanical parts of CITROEN vehicles painted black.

Not miscible or compatible with synthetic fluids.

BENEFITS

- **LHM S** was completed for CITROEN vehicles according to the directives of this manufacturer.
- **LHM S** is miscible in all proportions with all the other LHM fluids.
- **LHM S** is compatible with the elastomers entering the mechanical parts of CITROEN vehicles painted GREEN.

PERFORMANCES

LHM S corresponds with PSA CITROEN specifications: PSA B71 2710 (LHM Plus)

CHARACTERISTICS

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
Colour	-	Visual	Green
Specific gravity at 20°C	kg/m ³	NF T 60-101	833
Kinematic viscosity at 40°C	mm ² /s	NF T 60-100	18,2
Kinematic viscosity at 100°C	mm ² /s	NF T 60-100	6,2
Kinematic viscosity at -40°C	mm ² /s	NF T 60-100	1126
Viscosity index	-	NF T 60-136	340
Pour point	°C	NF T 60-105	< -60
Flash point	°C	NF T 60-118	> 116

This typical data is given for information only

HEALTH, SAFETY AND ENVIRONMENT

Elimination must be carried out to conform to the rules set for the disposal of used hydraulic liquid.

Must be stored away from bad weather.

Should you need further details, our Technical Department remains at your disposal.