

MARINE 350 S

HIGH PERFORMANCE MONOGRADE OILS



MARINE RANGE

4 STROKE ENGINE
SAE 30
SAE 40

STANDARDS & SPECIFICATIONS

API CF
WARTSILA (SAE grade 40)
BAUDOUIN (SAE grade 30)



APPLICATIONS

MARINE 350 S oils have been specially developed to lubricate high performance diesel engines operating under all conditions, and particularly with fuels that have a high sulphur content.

BENEFITS

MARINE 350 S oils are high performance monograde oils with the following advantages :

- Very high stability and resistance to oxidation,
- High level of detergency and dispersivity,
- High alkalinity reserve,
- Excellent anti-corrosion and anti-rust protection,
- Very good anti-wear properties.

PERFORMANCES

PERFORMANCE LEVELS

API CF
MIL-L-2104 E
CUMMINS
MAN ES moteur 4T (SAE grade 40)
WARTSILA (SAE grade 40)
BAUDOUIN (SAE grade 30)

CHARACTERISTICS

| CHARACTERISTICS | UNITS | METHODS | TYPICAL DATA | |
|------------------------------|--------------------|-------------|--------------|--------|
| | | | SAE 30 | SAE 40 |
| SAE grade | - | - | SAE 30 | SAE 40 |
| Specific gravity at 15°C | kg/m ³ | NF T 60-101 | 898 | 909 |
| Kinematic viscosity at 40°C | mm ² /s | NF T 60-100 | 96,5 | 144 |
| Kinematic viscosity at 100°C | mm ² /s | NF T 60-100 | 11 | 14,5 |
| Viscosity index | - | NF T 60-136 | 98 | 99 |
| Pour point | °C | NF T 60-105 | -30 | -27 |
| Flash point | °C | NF T 60-118 | 244 | 258 |
| Sulfated ash content | % weight | NF T 60-143 | 2,61 | 5,01 |
| TBN | mgKOH/g | ASTM D 2896 | 20,4 | 40,1 |

This typical data is given for information only



HEALTH, SAFETY AND ENVIRONMENT

Elimination must be carried out to conform to the rules set for the disposal of used lubricants.

Must be stored away from bad weather.

Should you need further details, our Technical Department remains at your entire disposal.