

MATIC ATF

FLUID FOR AUTOMATIC GEAR-BOXES



TRANSMISSION RANGE
AUTOMATIC GEAR-BOXES
MINERAL

Mineral

Semi-synthetic

100% synthetic

MANUFACTURING STANDARDS
GM AQ.ATF Type A Suffix A
MB 236.2

Oxidation resistance



Anti-wear level



APPLICATIONS

MATIC ATF is a Type A Suffix A hydraulic fluid especially developed for lubricating clutches and automatic or semi-automatic gearboxes of cars, engines, industrial and commercial vehicles.

BENEFITS

- High viscosity index
- Excellent oxidation resistance
- Quick demulsion
- Low pour point

PERFORMANCE

PERFORMANCE LEVELS

GM AQ.ATF Type A Suffix A
MB 236.2

CHARACTERISTICS

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
ISO grade	-	-	32
Colour	-	Visual	red
Density at 15°C	kg/m ³	NF T 60101	866
Kinematic viscosity at 40°C	mm ² /s	NF T 60100	38.1
Kinematic viscosity at 100°C	mm ² /s	NF T 60100	7.2
Viscosity index	-	NF T 60136	155
Brookfield viscosity at -40°C	mPa.s	NF T 60152	50 400
Pour point	°C	NF T 60105	-48
Flash point	°C	NF T 60118	224

The above data are provided on an indicative basis only.

HEALTH, SAFETY AND ENVIRONMENT

Disposal must be carried out in compliance with the rules governing the disposal of used lubricants.

Must be stored away from bad weather conditions.

For further details, our Technical Department is available to assist you.