



MOTOR 2 D SAE 40

MONOGRADE OIL FOR DIESEL 2 STROKE ENGINES



INDUSTRIAL VEHICLES RANGE

ENGINE
MINERAL
SAE 40

STANDARDS AND SPECIFICATIONS

API CF2/CD2
DETROIT DIESEL

Mineral

Semi-
synthetic100%
synthetic

APPLICATIONS

MOTOR 2 D SAE 40 is suitable for any **Diesel 2 stroke engines** and for separated lubrication.

MOTOR 2 D SAE 40 is also suitable for certain transmission and gear boxes.

BENEFITS

MOTOR 2 D SAE 40 offers the following characteristics :

- High viscosity stability and good resistance to oxidation
- Improved anti-corrosion and anti-wear power exceeding engine's life
- Good detergent and dispersant power for perfect engine cleanliness

PERFORMANCES

PERFORMANCE LEVELS

API CF2/CD2

DETROIT DIESEL

CHARACTERISTICS

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
SAE grade	-	-	SAE 40
Specific gravity at 15°C	kg/m ³	NF T 60-101	893
Kinematic viscosity at 40°C	mm ² /s	NF T 60-100	137
Kinematic viscosity at 100°C	mm ² /s	NF T 60-100	14,4
Viscosity index	-	NF T 60-136	103
Pour point	°C	NF T 60-105	-24
Flash point	°C	NF T 60-118	238
Sulfated ashes content	% weight	NF T 60143	0,80
TBN	mg KOH/g	ASTM D 2896	7

This typical data is given for information only



HEALTH, SAFETY AND ENVIRONMENT

Elimination must be carried out to conform to the rules set for the disposal of used lubricants.

Must be stored away from bad weather.

Should you need further details, our Technical Department remains at your entire disposal.