



# MOUV GREEN

BIODEGRADABLE MACHINE OIL

## APPLICATIONS

**MOUV GREEN** is an oil for the movements of machines, chain lubrication and more, when there is a risk of accidental pollution of the environment.

**MOUV GREEN 100** is particularly suitable for lubricating vacuum pumps.

## BENEFITS

- Very high viscosity index for withstanding high temperature variations
- Low pour point
- **MOUV GREEN 100** has a higher resistance to oxidation and superior anti-corrosion protection of ferrous and non-ferrous metals.

## CHARACTERISTICS

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA	
ISO grade	-	-	<b>68</b>	<b>100</b>
Density at 20°C	kg/m <sup>3</sup>	NF T 60-101	919	
Kinematic viscosity at 40°C	mm <sup>2</sup> /s	NF T 60-100	62.4	94.6
Kinematic viscosity at 100°C	mm <sup>2</sup> /s	NF T 60-100	13.4	19.6
Viscosity index	-	NF T 60-136	222	232
Flash point	°C	NF T 60-118	324	318
Pour point	°C	NF T 60-105	-30	-18
Biodegradability	%	CEC-L33-A-93	> 98	> 80
Biodegradability	%	OECD 301B	78	

*The typical characteristics provided are only approximate values*

## HEALTH, SAFETY AND ENVIRONMENT

Disposal must comply with applicable regulations pertaining to the disposal of used oils.

**Store in a sheltered area.**

Our technical department is available to provide advice if needed.

Unil  
LUBRIFIANTS  
opal  
MOUV GREEN