



## OPALJET ELLYPSE 0W20

FULL SYNTHETIC LUBRICANT SPECIFIC PSA



## LIGHT VEHICLE RANGE

ENGINE  
FULL SYNTHETIC  
SAE 0W-20

## STANDARDS AND SPECIFICATIONS

ACEA C5-21  
API SP  
PSA B71 2010



## APPLICATIONS

OPALJET ELLYPSE 0W20 is a full synthetic oil labelled "ECO-FUEL", designed to meet the most demanding requirements of modern vehicle engines, while achieving fuel savings

OPALJET ELLYPSE 0W20 is suitable for PSA engines: PureTech; Hybrids, the latest turbo engines from opel group.

## ADVANTAGES

- Low cold viscosity (SAE 0W grade) allowing the fluid to circulate more quickly in the engine while ensuring excellent engine protection against wear:
  - Fuel savings and reduced CO2 emissions
- Has exceptional natural characteristics: Shear resistance, low volatility
- Protection of post-treatment systems thanks to low ash, sulphur and phosphorus content: improves the longevity of particulate filters (PFs) and protects catalysts.

## PERFORMANCES

APPROVALS (1) | PSA B71 2010

## PERFORMANCE LEVEL

ACEA 2021: C5, C6  
API: SN-Plus / SP

FIAT 9.55535-DM1

(1) Approval certificate available on request

## CHARACTERISTICS

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
SAE grade	-	-	0W-20
Density at 20°C	kg/m <sup>3</sup>	NF T 60-101	844
Kinematic viscosity at 40°C	mm <sup>2</sup> /s	NF T 60-100	43
Kinematic viscosity at 100°C	mm <sup>2</sup> /s	NF T 60-100	8.2
Pour point	°C	NF T 60-105	- 48
Flash point	°C	NF T 60-118	233
TBN	mgKOH/g	ASTM D 2896	10.4

*The average characteristics are given for information only*

## HYGIENE, SAFETY AND ENVIRONMENT

Disposal must be carried out in accordance with the regulations in force on the elimination of used oils.

**Store protected from bad weather.**

[www.unil-opal.com](http://www.unil-opal.com)

Our technical department is at your disposal to provide you with the necessary advice