



OPALJET ELLYPSE 0W20

FULL SYNTHETIC LUBRICANT SPECIFIC PSA



LIGHT VEHICLE RANGE
ENGINE
FULL SYNTHETIC
SAE 0W-20

STANDARDS AND SPECIFICATIONS
ACEA C5-21
API SP
PSA B71 2010

APPLICATIONS

OPALJET ELLYPSE 0W20 is a full synthetic oil labelled “ECO-FUEL”, designed to meet the most demanding requirements of modern vehicle engines, while achieving fuel savings

OPALJET ELLYPSE 0W20 is suitable for recent PSA DV5R (after 02/2023) and EB2DT engines equipped with the latest technologies: Blue HDi, PureTech Stop & Start systems and hybrid engines.

ADVANTAGES

- Low cold viscosity (SAE 0W grade) allowing the fluid to circulate more quickly in the engine while ensuring excellent engine protection against wear:
 - Fuel savings and reduced CO2 emissions
- Has exceptional natural characteristics: Shear resistance, low volatility
- Protection of post-treatment systems thanks to low ash, sulphur and phosphorus content: improves the longevity of particulate filters (PFs) and protects catalysts.

PERFORMANCES

APPROVALS (1) | PSA B71 2010

PERFORMANCE LEVEL

ACEA 2021: C5, C6

API: SN-Plus / SP

FIAT 9.55535-DM1

(1) Approval certificate available on request

CHARACTERISTICS

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
SAE grade	-	-	0W-20
Density at 20°C	kg/m ³	NF T 60-101	844
Kinematic viscosity at 40°C	mm ² /s	NF T 60-100	43
Kinematic viscosity at 100°C	mm ² /s	NF T 60-100	8.2
Pour point	°C	NF T 60-105	- 48
Flash point	°C	NF T 60-118	233
TBN	mgKOH/g	ASTM D 2896	10.4

The average characteristics are given for information only

HYGIENE, SAFETY AND ENVIRONMENT

Disposal must be carried out in accordance with the regulations in force on the elimination of used oils.

Store protected from bad weather.

www.unil-opal.com

Our technical department is at your disposal to provide you with the necessary advice