



OPALJET POWER 5W30

100% SYNTHETIC OIL FOR FORD VEHICLES



LIGHT VEHICLES RANGE

ENGINE
100% SYNTHETIC
SAE 5W-30

Mineral

Semi-synthetic

100%
synthetic

STANDARDS AND SPECIFICATIONS

ACEA A5/B5-21
API SL
FORD WSS-M2C913-D
STJLR.03.5003

Engine cleanliness

Oxidation resistance

Shear stability



APPLICATIONS

OPALJET POWER 5W30 is a top of the range oil providing a perfect protection of FORD engines.

Attention: this oil is not adapted to the lubrication of some engines (not requiring the norms mentioned in the PERFORMANCE DETAILS paragraph) : in case of doubt, please contact us.

BENEFITS

5W30 grade of **OPALJET POWER 5W30** allows a more significant fuel economy:

- « 5W »: protects your engine when starting from the extreme cold (-30°C)
- « 30 »: is more fluid when warm than the majority of oils on the market (SAE 40 grade when warm) to optimize the engine's mechanical performance. The SAE 30 grade provides good lubrication without causing any significant energy loss.

OPALJET POWER 5W30 allows to keep the engine clean
OPALJET POWER 5W30 provides fuel economy and low CO₂ emissions
OPALJET POWER 5W30 insures better protection against biofuel dilution

PERFORMANCES

APPROVALS (1) | FORD WSS-M2C913-D

PERFORMANCE LEVELS

ACEA A5/B5-21
API SL
RN 0700
STJLR.03.5003

(1) Approval certificates available on request

OPAL
5W30
OPAL
5W30
OPAL
5W30



CHARACTERISTICS

| CHARACTERISTICS | UNITS | METHODS | TYPICAL DATA |
|------------------------------|--------------------|---------------|--------------|
| SAE grade | - | - | 5W-30 |
| Specific gravity at 15°C | kg/m ³ | NF T 60-101 | 880 |
| Kinematic viscosity at 40°C | mm ² /s | NF T 60-100 | 52,4 |
| Kinematic viscosity at 100°C | mm ² /s | NF T 60-100 | 9,5 |
| Viscosity index | - | NF T 60-136 | 167 |
| Flash point | °C | NF T 60-118 | > 200 |
| CCS viscosity at -30°C | mPa.s | ASTM D 5293 | 4 010 |
| Noack volatility | % weight | CEC-L-40-A-93 | 13 |
| Sulfated ash content | % weight | NF T 60-143 | 1,1 |
| TBN | mg KOH/g | ASTM D 2896 | 9,4 |

This typical data is given for information only

HEALTH, SAFETY AND ENVIRONMENT

Elimination must be carried out to conform to the rules set for the disposal of used lubricants.

Must be stored away from bad weather.

Should you need further details, our Technical Department remains at your entire disposal.