



OPALPERF COMPETITION 10W60

100% SYNTHETIC LUBRICANT FOR COMPETITION ENGINES



LIGHT VEHICLES RANGE
ENGINE
100% SYNTHETIC
SAE 10W-60

STANDARDS AND SPECIFICATIONS
ACEA A3/B4
API SN/CF

Mineral

Semi-synthetic

100%
synthetic

Engine cleanliness

Oxidation resistance

Shear stability



APPLICATIONS

OPALPERF COMPETITION 10W60 is an oil elaborated to respond to the most severe requirements of competition car engines.

OPALPERF COMPETITION 10W60 is an 100% synthetic lubricant formulated with polyalphaolefins (PAO) and esters of a high molecular weight ensuring perfect protection of lubricated parts whatever the constraints these parts are submitted to.

OPALPERF COMPETITION 10W60 is formulated for gasoline engines, turbocharged-or-not, multivalve-or-not. Is also suitable for Diesel engines

BENEFITS

- Excellent shear resistance : oil film maintained under severe service conditions
- Good protection of the engine at start-up
- keeping the engine clean : excellent detergent-dispersant properties
- Reinforced thermal stability preventing deposits formation

PERFORMANCES

PERFORMANCE LEVELS | ACEA A3/B4-23
API SN/CF

EXPERIENCE IN OPERATIONAL USE

ALFA ROMEO
BMW
FERRARI
LOTUS
MASERATI
OPEL



CHARACTERISTICS

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
SAE grade	-	-	10W-60
Specific gravity at 20°C	kg/m ³	NF T 60-101	852
Kinematic viscosity at 40°C	mm ² /s	NF T 60-100	161
Kinematic viscosity at 100°C	mm ² /s	NF T 60-100	23.9
Viscosity index	-	NF T 60-136	180
Pour point	°C	NF T 60-105	-51
Flash point	°C	NF T 60-118	242
CCS viscosity at -25°C	mPa.s	ASTM D 5293	6000

This typical data is given for information only

HEALTH, SAFETY AND ENVIRONMENT

Elimination must be carried out to conform to the rules set for the disposal of used lubricants.

Must be stored away from bad weather.

Should you need further details, our Technical Department remains at your entire disposal.