



OPALPERF LONGLIFE DEX 1.2 FE 5W30

FULL SYNTHETIC LUBRICANT FOR GENERAL MOTORS



LIGHT-DUTY VEHICLES RANGE

ENGINE
FULL SYNTHETIC
SAE 5W-30

Mineral

Semi-synthetic

Full synthetic

STANDARDS AND SPECIFICATIONS

API SP-RC
GM DEXOS 1 GEN 2
ILSAC GF-6A
FORD WSS-M2C-946A
FORD WSS-M2C-946-B1

Engine cleanliness

Oxidation resistance

Shear stability

APPLICATIONS

OPALPERF LONGLIFE DEX 1.2 FE 5W30 is very high performance multigrade oil, specially formulated for modern petrol engines, with or without direct injection, and sensitive to Low Speed Pre-Ignition (L.S.P.I.):

BENEFITS

- 5W30 grade protects your engine when starting in cold weather (-30°C) and significantly reduces fuel consumption.
- **OPALPERF LONGLIFE DEX 1.2 FE 5W30** has a formulation using detergents containing magnesium to limit the risks of L.S.P.I. compared to the exclusive use of calcium-based detergents.
- **OPALPERF LONGLIFE DEX 1.2 FE 5W30** protects turbocharged GDI engines
- **OPALPERF LONGLIFE DEX 1.2 FE 5W30** has state-of-the-art additives to cool, lubricate and clean the engine to reduce wear and maximise engine life.

PERFORMANCES

PERFORMANCE LEVELS

API SN-Plus / SP / SP-RC
 CHRYSLER MS 6395
 FORD WSS-M2C-946A
 FORD WSS-M2C-946-B1
 GM 6094M
 GM DEXOS 1 GEN 2
 ILSAC GF-5 / GF-6A
 OPEL OV0401547-D30

OPAL
7W30
7W30
7W30
7W30



CHARACTERISTICS

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
SAE grade	-	-	5W-30
Density at 15°C	kg/m ³	NFT 60-101	844
Kinematic viscosity at 40°C	mm ² /s	NF T 60-100	60.9
Kinematic viscosity at 100°C	mm ² /s	NF T 60-100	10.8
Viscosity index	-	NF T 60-136	170
Pour point	°C	NF T 60-105	-36
Flash point	°C	NF T 60-118	225
CCS viscosity at -30°C	mPa.s	ASTM D 5293	3501

The average specifications provided are approximate values

HYGIENE, SAFETY AND ENVIRONMENT

Disposal must be carried out in compliance with applicable rules for the waste disposal of used oil.

Keep away from bad weather conditions.

Our technical department is available to give you any advice you may need.