



PERFORMANCE MOTEUR DIESEL

INJECTOR AND FUEL CIRCUIT CLEANING ADDITIVE



APPLICATIONS

PERFORMANCE MOTEUR DIESEL, a multifunction synthetic additive for diesel fuel, is a treatment for the admission system including the valves and the combustion chambers.

It is recommended for all vehicles (including those with a catalytic converter, a particle filter or direct fuel injection) and is particularly recommended for those with EGR (Exhaust Gas Recirculation).

BENEFITS

PERFORMANCE MOTEUR DIESEL contains a constituent that optimizes the combustion process (by increasing the cetane number by 1.5 to 2 points), and which therefore:

- Increases power,
- Reduces fuel consumption,
- Reduces exhaust smoke.

PERFORMANCE MOTEUR DIESEL also contains an admission system cleaner which cleans and lubricates the injectors, the valves and the combustion chambers, and which therefore:

- Stabilizes engine idle,
- Reduces fuel consumption.

The components of **PERFORMANCE MOTEUR DIESEL** also neutralize the condensation caused by the mixing of warm and cold fuels in the tank, and the bacteria present in the water at the bottom of the fuel storage tank, and this:

- Prevents deposits,
- Protects the admission system from corrosion.

Together, all of these actions ensure a **noticeable increase in the life of the engine**, and particularly injection systems which are affected by the reduction in fuel sulfur content.

USAGE

- Preventive: 1 liter for 600 liters of fuel.
- Corrective: 1 liter for 200 liters of fuel.
- On light vehicles, when **PERFORMANCE MOTEUR DIESEL** is used for the first time or in case of considerable deposits, add one complete unit of **PERFORMANCE MOTEUR DIESEL** to each full tank of fuel the first two times the tank is filled, then every 5,000 km.

CHARACTERISTICS

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
Specific gravity at 15°C	Kg/m ³	NF T 60-101	893
Kinematic viscosity at 40°C	mm ² /s	NF T 60-100	1,28
Open cup flash point	°C	NF T 60-118	58

This typical data is given for information only

HEALTH, SAFETY AND ENVIRONMENT

Elimination must be carried out to conform to the rules set for the disposal of used mineral oils.

Must be stored away from bad weather.

Should you need further details, our Technical Department remains at your disposal.