



# PRODUIT DE RINCAGE

CLEANING ADDITIVE FOR HEAT TRANSFER FLUID CIRCUITS



## APPLICATIONS

**PRODUIT DE RINCAGE** cleans the inside of heat transfer fluid circuits quickly and easily.

**PRODUIT DE RINCAGE** is suitable for heating circuits containing a mineral heat transfer fluid.

## BENEFITS

- Removes all impurities such as gums and varnish from the circuit.
- Improves oil circulation.
- Keeps particles in suspension before draining.

## USE

**WARNING:** use at a dosage of 10% in the oil to be drained.

- Pour **PRODUIT DE RINCAGE** into used oil.
- Run the circuit so that the heat transfer fluid and additive heat up for +30 minutes.
- Drain quickly before the oil cools completely.
- Fill the housing with new oil.

## CHARACTERISTICS

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
Density at 15°C	Kg/m <sup>3</sup>	NF T 60-101	887
Kinematic viscosity at 40°C	mm <sup>2</sup> /s	NF T 60-100	8
Kinematic viscosity at 100°C	mm <sup>2</sup> /s	NF T 60-100	3
Flash point	°C	NF T 60103	140

*The average specifications provided are approximate values*

## HEALTH, SAFETY AND ENVIRONMENT

Disposal must be carried out in compliance with applicable rules for the disposal of used oil.

**Store in an area sheltered from bad weather.**

Our technical department is available to give you any advice you may need.