

PROFIL B 120 EV







APPLICATIONS

PROFIL B 120 EV is generally used for deformation operations such as: profiling, cutting and punching on thin metal sheets.

PROFIL B 120 EV aims to completely or partially eliminate cleaning and/or degreasing operations on the resulting components.

PROFIL B 120 EV is easy to apply using standard micro-projection procedures or spraying or application with a roller, felt or drop by drop.

BENEFITS

- > Pleasant for operators to use because of its volatile non toxic nature : Chlorine free
- Non-flammable product: Safe and flexible to use without restrictions. Fewer storage and transport constraints
- The kind of the components allows very difficult operations to be conducted with an imperceptible residual film, which authorizes ulteriorly, after evaporation, all weld operations.
- Can be used on all metals.

CHARACTERISTICS

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
Specific gravity at 20°C	kg/m³	NF T 60 172	783
Flash point in close cup	°C	NF M 07 011	69

This typical data is given for information only

しなり

HEALTH, SAFETY AND ENVIRONMENT

Avoid contact with the skin

Elimination must be carried out to conform to the rules set for the disposal of used lubricants.

Must be stored away from bad weather.

Should you need further details, our Technical Department remains at your entire disposal

