



PROFIL B 50 EV

CHLORINE FREE VOLATILE METAL SHAPING FLUID



APPLICATIONS

PROFIL B 50 EV is generally used for deformation operations such as: profiling, cutting and punching on thin metal sheets.

PROFIL B 50 EV aims to completely or partially eliminate cleaning and/or degreasing operations on the resulting components.

PROFIL B 50 EV allows very difficult operations to be conducted with an imperceptible residual film, which authorizes ulteriorly, after evaporation, all weld operations.

BENEFITS

- **Pleasant for operators to use** because of its volatile non toxic nature : Chlorine free
- **Non-flammable** product : Safe and flexible to use without restrictions. " Fewer storage and transport constraints
- High performances dry extract.
- Can be used on all metals.
- **PROFIL B 50 EV** is easy to apply using standard micro-projection procedures or spraying or application with a roller, felt or drop by drop.

CHARACTERISTICS

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
Specific gravity at 20°C	Kg/m3	NF T 60 172	774
Flash point in close cup	°C	NF M 07 011	67

This typical data is given for information only

HEALTH, SAFETY AND ENVIRONMENT

Avoid contact with the skin

Elimination must be carried out to conform to the rules set for the disposal of used lubricants.

Must be stored away from bad weather.

Should you need further details, our Technical Department remains at your entire disposal.

OPAL
UNIL
UNIL
OPAL
UNIL