

PROFIL X 150 EV

CHLORINE FREE VOLATILE METAL SHAPING FLUID



APPLICATIONS

PROFIL X 150 EV is generally used for operations such as : stamping, shaping, cutting and punching on metal sheets.

PROFIL X 150 EV aims to completely or partially eliminate cleaning and/or degreasing operations on the resulting components.

PROFIL X 150 EV allows very difficult operations to be conducted with an imperceptible residual film. Provides durable protection against corrosion between operations.

PROFIL X 150 EV is easy to apply using standard aerosol procedures, or spraying, or application with a roller, cloth or drop-by-drop.

BENEFITS

- **Pleasant for operators to use** because of its volatile non-toxic nature : whitout chlorine.
- **Non-flammable** product : safe and flexible to use without restrictions. Fewer storage and transport constraints
- Dry extract with very high extreme-pressure performances.
- **Metal protection** : Anti-corrosion additive.
- Can be used on all metals

CHARACTERISTICS

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
Specific gravity at 20°C	Kg/m3	NF T 60 172	794
Flash point in close cup	°C	NF M 07 011	68

This typical data is given for information only

HEALTH, SAFETY AND ENVIRONMENT

Avoid contact with the skin

Elimination must be carried out to conform to the rules set for the disposal of used lubricants.

Must be stored away from bad weather.

Should you need further details, our Technical Department remains at your entire disposal