



PROTECT CX 24

LONG-TERM, SOLVENT-FREE HYDROFUGEANT PROTECTION FLUID



APPLICATIONS

PROTECT CX 24 is a non-corrosive, solvent-free fluid. Given the high flash point, safety conditions are optimal.

PROTECT CX 24 leaves a thin WAX film on the parts.

BENEFITS

Its hydrofugeant (water-repellent) property makes it possible to recommend very long-term storage time.

USE

By brushing, dipping or spraying.

Film can be eliminated by a solvent type UNIL OPAL SOLV'CLEANER B 70 or by a detergent type UNIL OPAL SHP Multi HP.

PERFORMANCE

Duration of protection:

- Indoors: 24 months - Outdoors: 6 months - Bad weather conditions: 1 month

These protection data are only for indicative purposes. They depend on specific storage conditions (moisture content, type of atmosphere, etc.).

Complies with ISO L 6743-8 RDD standard.

CHARACTERISTICS

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
Covering power	m ² /l	-	125
Film thickness	micron	-	10
Kinematic viscosity at 40°C	mm ² /s	NF T 60100	22.8.
Density at 15°C	kg/m ³	NF T 60101	850
Appearance and colour	-		Waxy and brown
Flash Point	°C	NF T 60118	137
Salt spray	h	NF A 05-101	96

The average specifications provided are approximate values

HYGIENE, SAFETY AND ENVIRONMENT

The absence of volatile solvents does not require special precautions for use.

Store in a FROST-FREE environment and away from BAD WEATHER conditions.

Waxy product, some of which can settle. In this case, use the oily phase

OPAL
OPAL
OPAL
OPAL
OPAL