




PROTECT HX 3

SOLVENT-FREE WATER-REPELLENT PROTECTION LIQUID



APPLICATIONS

PROTECT HX 3 is a solvent-free anti-corrosion liquid. It has the best safety conditions thanks to its high flash point.

PROTECT HX 3 leaves a fine OILY film on parts.

BENEFITS

Its dewatering character means this product is recommended for short-term storage under shelter and for protection between two machining operations.

USAGE

Brush, soak or spray on.

Remove the film using a UNIL OPAL SOLV'CLEANER B 70 type solvent or a UNIL OPAL SHP Multi HP type detergent.

PERFORMANCE

Protection time :

- Indoors : 3 months - Outdoors under shelter : 1,5 months - Bad weather : not recommended

This protection data is for information purposes only. It depends on the exact storage conditions (humidity rate, atmosphere rate, etc.).

Conforms to standard ISO L 6743-8 RDD.

CHARACTERISTICS

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
Covering power	m ² /l	-	650
Film thickness	micron	-	1.5
Kinematic viscosity at 40°C	mm ² /s	NF T 60100	4.3
Specific gravity at 15°C	Kg/m ³	NF T 60101	825
Appearance and colour	-		Viscous liquid, brown
Flash point	°C	NF T 60118	125
Salt mist	h	NF A 05-101	24

This typical data is given for information only

HEALTH, SAFETY AND ENVIRONMENT

The absence of any volatile solvents means that no special usage precautions are required.

Store away from frost and bad weather.

OPAL
OPAL
OPAL
OPAL
OPAL