




PROTECT SC 18

LONG-LASTING HYDROFUGEANT PROTECTIVE FLUID WITH GREASY WAX FILM



APPLICATIONS

PROTECT SC 18 is an anti-corrosion fluid, which contains a volatile non-chlorinated SOLVENT. **PROTECT SC 18** leaves a greasy wax film after the solvent evaporates.

BENEFITS

Its hydrofugeant (dewatering) and quick drying properties allow it to be quickly applied to any finished part in long term storage outdoors

USE

By brushing, dipping or spraying (word of caution: 2 bar maximum). Film can be eliminated by a solvent type UNIL OPAL SOLV'CLEANER B 70 or by a detergent type UNIL OPAL SHP Multi HP.

PERFORMANCE

Duration of protection:
- Indoors: 18 months - Outdoors under a shelter: 12 months - Bad weather conditions: 6 months

These protection data are only for indicative purposes. They depend on specific storage conditions (moisture content, type of atmosphere, etc.).

Complies with ISO L 6743-8 RFF standard.

CHARACTERISTICS

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
Covering power	m ² /kg	-	30-40
Film thickness	micron	-	8
Drying time at 20°C	h		0.75
Density at 15°C	kg/m ³	NF T 60101	830
Appearance and colour	-		Greasy and dark brown
Flash Point	°C	NF T 60118	35
Salt spray	h	NF A 05-101	250

The average specifications provided are approximate values

UNIL OPAL



HYGIENE, SAFETY AND ENVIRONMENT

Caution: FLAMMABLE product. Do not use near flames, sparks or electric motors.

Store in a FROST-FREE environment and away from BAD WEATHER conditions.

Avoid excessive concentration of vapors in the air at the workplace.

Product containing solvent: avoid leaving cans open too long (because of evaporation).

Waxy product, some of which can settle. In this case, use the oily phase.