

# PROTEC BF

LIQUID ANTI-SPLIT AND ANTI CRACK PRODUCT



## APPLICATIONS

**PROTEC BF** is a highly concentrated paraffin emulsion.

After drying, **PROTEC BF** leaves a clear, impermeable wax film on treated surfaces.

Hard woods such as beech, oak and other species must contain a certain quantity of water before they are worked. If not, splits and cracks may appear before or during wood-working operations. Applying **PROTEC BF** prevents wood from drying out too quickly, leading to the formation of splits.

## BENEFITS

- When sprayed onto the end of logs (edge), enables wood to be preserved for several months without cracking.
- Recommended before drying (free or baked) to avoid splits appearing.
- Rapid seasoning of wood
- Water-repellent
- Do not change wood's natural colour

## USAGE

- The product must be stored at a minimum of +5°C; below this temperature, the product separates and is irretrievably lost.
- Shake before use.
- Use undiluted.
- Brush or spray on

## CHARACTERISTICS

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
Colour		Visual	White
Specific gravity at 20°C	Kg/m <sup>3</sup>	NF T 60101	915
pH	-	-	9.5
Dry matter	%	-	46

*This typical data is given for information only*

## HEALTH, SAFETY AND ENVIRONMENT

Disposal must be carried out in compliance with the rules governing the disposal of used lubricants.

**Store away from frost and bad weather.**

For further details, our Technical Department is available to assist you.