

PROTHYDRO VSI 2071

HYDRAULIC ANTI-RUST PROTECTION FLUID



APPLICATIONS

PROTHYDRO VSI 2071 specially formulated for manufacturers of hydraulic components and equipment.

PROTHYDRO VSI 2071 provides protection against internal corrosion during prolonged stoppage, whether or not the equipment has been drained. Simply leave a small quantity of the product in the component or circuit.

BENEFITS

- High thermal stability
- Passive towards metals and elastomers
- Even after prolonged storage, it does not alter the characteristics of conventional hydraulic fluids.

PERFORMANCES

PERFORMANCE LEVELS

NF E 48602/HM
DIN 51524-2/HLP

CHARACTERISTICS

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
Color	-	Visual	Light Yellow
Density at 15°C	kg/m ³	NF T 60-101	873
Kinematic viscosity at 40°C	mm ² /s	NF T 60-100	45
Kinematic viscosity at 100°C	mm ² /s	NF T 60-100	6.7
Viscosity index	-	NF T 60-136	103
Flash point	°C	NF T 60-118	214
Pour point	°C	NF T 60-105	-27

The typical data provided are only approximate values

HEALTH, SAFETY AND ENVIRONMENT

Disposal must comply with applicable regulations pertaining to the disposal of used oils.

Store in a sheltered area.

Our technical department is available to provide advice if needed.