




SCOOT 2T

SEMI-SYNTHETIC OIL FOR 2-STROKE SCOOTERS



SCOOTER RANGE
2-STROKE ENGINE
SEMI-SYNTHETIC



Engine cleanliness



Performance



Smoke



INTERNATIONAL STANDARDS
API TC

APPLICATIONS

SCOOT 2T is a semi-synthetic oil specially elaborated for lubricating small-capacity air-cooled 2-stroke engines: scooters, mopeds.

SCOOT 2T is mixed with the fuel according to a fuel-to-oil ratio of 50:1 or less, depending on the manufacturer's recommendations. May also be used in engines where the oil is injected separately.

BENEFITS

- **Low sulfated ash content** that protects against pre-ignition phenomena at high temperatures.
- **High detergent properties** that eliminate any deposits and residues resulting from combustion thereby keeping the transfer and exhaust ports clean.
- **Maximum protection against corrosion.**

PERFORMANCE

LEVEL OF PERFORMANCE | API TC

OPAL
UNIL
OPAL
UNIL



CHARACTERISTICS

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
Colour	-	visual	Red
Density at 15°C	kg/m3	NF T 60101	882
Kinematic viscosity at 40°C	mm ² /s	NF T 60100	99.3
Kinematic viscosity at 100°C	mm ² /s	NF T 60100	12
Viscosity index	-	NF T 60136	111
Flash point	°C	NF T 60118	150
Sulfated ash content	% mass	NFT 60143	0.08
TBN	mg KOH/g	ASTM D 2896	1.01

The average specifications provided are approximate values

HEALTH, SAFETY AND ENVIRONMENT

Disposal must be carried out in compliance with applicable rules for the waste disposal of used oil.

Keep away from bad weather conditions.

Our technical department is at your disposal to give you the advice you require.

Unil
Opal