

# SOLV'CLEANER SR3

VERY FAST-DRYING DEGREASING SOLVENT



## APPLICATIONS

**SOLV'CLEANER SR3** is a CHLORINE-FREE hydrocarbon solvent suitable for degreasing mechanical parts made of any metal.

**SOLV'CLEANER SR3** is formulated from new oil bases. It is a very good alternative to 1,1,1-trichloroethane in its cold applications

**SOLV'CLEANER SR3** is recommended for cleaning machined parts and machine tools, tools and worktops.

**SOLV'CLEANER SR3** can be used in a dip tank, by flushing or runoff, by brushing or with a rag

## BENEFITS

- Low aromatic hydrocarbon content and odourless, it ensures protection for users.
- Excellent degreasing and evaporation qualities that ensure the degreasing of mechanical parts **between operations** or in **finishing** as well as **tooling**.
- High evaporation rate
- No corrosive action on degreased materials (ferrous and non-ferrous).

Does not contain chlorine and any other halogenated components: reduced costs for waste products

## CHARACTERISTICS

CHARACTERISTICS	UNITS	METHODS	AVERAGE VALUES
Colour	-	Visual	Colourless
Kinematic viscosity at 20°C	mm <sup>2</sup> /s	NF T 60100	1,3
Relative evaporation rate (n-butyl acetate = 1)	-	ASTM D 3539	0,56
Density at 20°C	kg/m <sup>3</sup>	NF T 60101	750
Flash point	°C	NF T 60118	24
Aniline point	°C	NF M 07021	65

*The typical characteristics provided are only approximate values*

## HEALTH, SAFETY AND ENVIRONMENT

### Flammable product

Harmful and may cause lung damage if swallowed, do not induce vomiting.  
Avoid contact with skin and do not inhale the vapours.

**Take the necessary precautions for use of a product whose closed cup flash point is between 21°C and 55°C**

Disposal after use must be carried out in accordance with current legislation.

### Store in an area sheltered from bad weather.

Our technical department is available to give you any advice you may need.