

SOLVANT NF CHLORINE-FREE CLEANING SOLVENT





APPLICATIONS

SOLVANT NF is a solvent for moulds, machined parts, machines, electric motors, chains, etc. It can be used with a brush, by spraying or soaking.

BENEFITS

- > It removes quickly and completely oils, greases, but also bitumen, tar and other surface deposits.
- It immediately and easily breaks down water-soluble dirt.
- > The optimal evaporation time allows the additive to act deeply and for long enough on the surfaces and parts to be cleaned to dissolve and remove dirt.
- Does not damage paint, varnish and rubber parts.
- Chlorine-free

WARNING! Carry out a compatibility test before using on plastic.

CHARACTERISTICS

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
Appearance	-	Visual	Clear
Туре	-	-	Hydrocarbons and acetones
Colour		Visual	Colourless
Specific gravity at 15°C	Kg/m³	NF T 60-101	694
Flash point	°C	NF T 60-118	-26
Self-ignition point	°C	ASTM A 659	>230

This typical data is given for information only

HEALTH, SAFETY AND ENVIRONMENT

Flammable product

Harmful and may cause lung damage if swallowed, do not induce vomiting.

Avoid contact with the skin and do not inhale the vapours.

Take the necessary precautions for use of a product whose closed cup flash point is below 21°C.

Disposal after use must be carried out in accordance with the legislation in force.

Keep away from bad weather conditions.

Our technical department is available to provide any advice if needed

