

SPECIAL CHAIN ULTRA

HIGHLY ADHESIVE LUBRICANT FOR CHAINS



APPLICATIONS

SPECIAL CHAIN ULTRA is used in LV, HV and mechanised agriculture garages and in motorcycle and bicycle repair shops. It is ideal for clean and simple lubrication of chains, hinges, bolts, springs, locks, articulated joints, battery terminals, slide rails, etc.

Temperature limits in use: -20 °C to +120 °C

BENEFITS

- Perfectly adhesive.
- Resistant to high pressures and temperatures.
- Provides high protection against corrosion by leaving a protective film on the part.
- Resistant to water projections.

PRODUCT CHARACTERISTICS

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
Colour	-	Visuelle	Beige
Type	-	-	Oil, organic thickener, anticorrosion agent, adhesive agent
Specific gravity at 20°C	kg/m ³	NF T 60-101	892
Consistency	NLGI	NF T 60-506	2
Dropping point	°C	NF T 60-102	149

This typical data is given for information only

AEROSOL CHARACTERISTICS

- Gross volume : 650 ml
- Net content : 500 ml
- Net weight : 327 g
- Weight of active product : 196 g
- Double ball valve for use in any position
- Supplied with 2 spray nozzles : 1 standard and 1 long.

HEALTH, SAFETY AND ENVIRONMENT

Only dispose of completely empty containers. Disposal after use must comply with current applicable regulations.

Store in an area protected from the weather.

Our technical department is available to help and advise you if needed.

Propellant gas: butane / propane (extremely flammable).