



# STOP-FUITES HYDRAULIQUE

ADDITIVE AGAINST LEAKING OIL



## APPLICATIONS

**STOP-FUITES HYDRAULIQUE** eliminates oil leaks caused by old gaskets in hydraulic circuits.

## BENEFITS

- **STOP-FUITES HYDRAULIQUE** is suitable for all mineral or synthetic oils.
- **STOP-FUITES HYDRAULIQUE** contains active synthetic components which regenerate gaskets and provide them with more flexibility and so eliminate leaks.
- **STOP-FUITES HYDRAULIQUE** does not effect the hydraulic circuit's lubrication and output.

## USAGE

- Use a 4% dose (4 liters for 100 liters).
- The product is best used after an oil change

## CHARACTERISTICS

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
Specific gravity at 20°C	Kg/m <sup>3</sup>	NF T 60101	924
Kinematic viscosity at 40°C	mm <sup>2</sup> /s	NF T 60100	23
Kinematic viscosity at 100°C	mm <sup>2</sup> /s	NF T 60100	3,7

*This typical data is given for information only*

## HEALTH, SAFETY AND ENVIRONMENT

Disposal after use must comply with current applicable regulations.

Store in an area protected from the weather.

Our technical department is available to help and advise you if needed.