

## TECHNICAL DATA SHEET

# **STOP-FUITES MOTEUR** ADDITIVE AGAINST OIL LEAKS

## **APPLICATIONS**

**STOP-FUITES MOTEUR** is an ester-based additive that is particularly recommended as an agent for causing gaskets to expand.

STOP-FUITES MOTEUR eliminates engine oil leaks and is suitable for petrol, diesel and LPG engines.

### **BENEFITS**

- Contains active synthetic components that regenerate the gaskets making them flexible so that they eliminate leaks
- > Does not affect the engine's lubrication

#### USE

ノノイ

**Yest** 

A dose of 300 ml allows to treat a crankcase containing up to 6L of oil. Preferably use the product after an oil change.

## **CHARACTERISTICS**

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
Colour	-	-	Light yellow
Density at 25°C	-	NF T 60-101	0.920
Viscosity at 40°C	mm²/s	NF T 60-100	7.9
Viscosity at 100°C	mm²/s	NF T 60-100	2.35
Flash point	°C	NF T 60-118	207

The average specifications provided are approximate values

## HEALTH, SAFETY AND ENVIRONMENT

Disposal must be carried out in compliance with applicable rules for the disposal of used oil.

#### Store in an area sheltered from bad weather.

Our technical department is available to give you any advice you may need.