



# SUPER MOYEUX

## EXTREME-PRESSURE GREASE FOR HUBS



### RANGE OF GREASES

NLGI 3  
EXTREME-PRESSURE  
WATER RESISTANT

Grade

3

-20°C/+130°C

### APPLICATIONS

Speed: medium to high  
Load: medium to high

Extreme-pressure level

## APPLICATIONS

Thanks to its Extreme-Pressure power and its grade (NLGI 3), **SUPER MOYEUX** can be used on all types of hubs including truck hubs.

This grease can be applied using a grease pump.

## BENEFITS

- Totally insoluble in water, even at boiling point or steam
- High resistance to distortion and shearing
- High protection against wear and corrosion

## CHARACTERISTICS

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
Soap	-	-	Lithium
Base fluid	-	-	Mineral oil
Texture	-	-	Smooth
Colour	-	Visual	Amber
NLGI Grade	-	ASTM D 217 mod	3
Drop point	°C	IP 396	> 190
Kinematic viscosity at 40°C	mm <sup>2</sup> /s	ASTM D 7152	130
Kinematic viscosity at 100°C	mm <sup>2</sup> /s	ASTM D 7152	12
Penetration 60 strokes	1/10 mm	ISO 2137	220-250
4-ball welding	Kg	ASTM D 2596	250
Water jet resistance at 79°C	%	ISO 11009	< 10
Emcor salt water test	-	ISO 11007	≤ 2 - 2
Temperature range	°C	-	-20 / +130

*The above data are provided on an indicative basis only.*

## HEALTH, SAFETY AND ENVIRONMENT

Disposal must be carried out in compliance with the rules governing the disposal of used lubricants.

**Must be stored away from bad weather conditions.**

For further details, our Technical Department is available to assist you.